



TESTA_e MINI

BENCHTOP ENVIRONMENTAL
AND TEMPERATURE TEST CHAMBERS




aralab






ARALAB is a company specialised in designing, developing, manufacturing and servicing of high quality climatic chambers and controlled environment rooms.

Since 1985 we have been perfecting ways to create and control temperature, humidity, light, air flow and many other environmental conditions.

Only the highest quality components are used to manufacture our chambers so customers can have the best equipment for their research and testing purposes.

Control the environment, Your own climate.



Testa_e temperature and humidity testing chambers offer precise and reproducible conditions for climatic and temperature testing in many industries.

COMMON APPLICATIONS INCLUDE:

- ENVIRONMENTAL TESTING
- ELECTRONICS, AUTOMOTIVE, AEROSPACE,
- BUILDING MATERIALS, MILITARY EQUIPMENT, MATERIALS IN GENERAL RESEARCH
- QUALITY CONTROL
- PRODUCTION FACILITIES

KEY FEATURES

- The most advanced technology in climate control
- Internal aerodynamic optimisation to ensure uniformity of climatic conditions
- Time saving features with easily configurable testing programs that can run, start and stop automatically
- Highly resistant stainless steel interior for maximum durability and easy cleaning
- Flexible interior with height adjustable and removable stainless steel shelves
- Nonpolluting construction and cooling system
- Compliant with international standards and requirements EN, IEC, DIN, ISO, NP and UNE



Certified ISO:9001 for its Quality Management System

TEMPERATURE AND HUMIDITY CONTROL RANGES

● ● ● ● MINI SERIES HIGH-LOW (HUMIDITY) CHAMBER


TESTA_E MINI CT 30 EP30

TEMPERATURE RANGE		-30°C to +150°C
TEMPERATURE FLUCTUATION		± 1°C
TEMPERATURE DEVIATION		± 2.0°C (temperature ≤ 100°C); ± 3.0°C (temperature > 100°C)
HUMIDITY RANGE		(25 to 98)% RH (20 to 85) °C
HUMIDITY DEVIATION		± 3.0% RH (> 75% RH); ± 5.0% RH (< 75% RH)
TEMPERATURE HEAT-UP RATE		-30°C to +150°C; ≤ 35min
TEMPERATURE PULL-DOWN RATE		+20°C to -25°C; ≤ 30min

TESTA_E MINI TT 30 E65

TEMPERATURE RANGE		-65°C to +150°C
TEMPERATURE FLUCTUATION		± 1°C
TEMPERATURE DEVIATION		± 2.0°C (temperature ≤ 100°C); ± 3.0°C (temperature > 100°C)
HUMIDITY RANGE		-
HUMIDITY DEVIATION		-
TEMPERATURE HEAT-UP RATE		-65°C to +150°C; ≤ 40min
TEMPERATURE PULL-DOWN RATE		+20°C to -60°C; ≤ 50min


TEMPERATURE AND HUMIDITY CHART OF TESTA_E MINI CT 30 EP30



DIMENSIONS AND DRAWINGS

● ● ● ● TESTA_E MINI CT 30 EP30 / TESTA_E MINI TT 30 E65

EXTERNAL DIMENSIONS (HxWxD) (mm)		805 x 480 x 850
INTERNAL DIMENSIONS (HxWxD) (mm)		400 x 300 x 250



INSTALLATION REQUIREMENTS

POWER SUPPLY	- AC220V/50Hz single-phase + protective grounding wire - AC(220±22)V (50±0.5)Hz - The earth resistance of protective grounding wire is less than 4Ω; - Users are required to provide air or power switches with appropriate capacity for equipment at the installation
POWER SUPPLY CAPACITY	2.3kW
MAXIMUM CURRENT	12 A
WATER FOR HUMIDITY GENERATOR (TESTA_E MINI CT 30 EP30 MODEL ONLY)	- Flow rate: ≥200kg/h - Water pressure: 0.1MPa ~ 0.25Mpa - The water filter system is provided with a pair of DN15 screwed joints.

EQUIPMENT DESCRIPTION

● ● ● ● CONSTRUCTION

INSULATION ENCLOSING STRUCTURE	- Outer wall: two-sided galvanized steel sheet with plastic-sprayed surface - Inner wall: SUS304 para AISI 304 - Thermal insulating material for chamber body: polyurethane foam + glass wool - Thermal insulating material for door: glass wool
AIR CONDITIONING CHANNEL	- Axial fan - Evaporator (dehumidifier), humidifier - Overheat protector - Water supply and drainage port dry boil protector - Heater - Dry-bulb temperature transducer - Wet-bulb temperature transducer, wet-bulb sink
DOOR	- Single hinged door with the hinge at the left side and knob on the right side - Dew-prevention device on window frame or door frame.
CABLE PORT	Oblong cable port: Ø50mm x 2, each at the left and right side of the chamber.
Control Panel	Controller display, Operation button, over-temperature protection setting device, USB interface
MACHINERY ROOM	- Refrigeration unit, water pan, drainage hole, condenser fan - Motor for adjusting channel
DISTRIBUTION CONTROL CABINET	- Leakage circuit breaker for general power supply - Distribution panel - Measuring device (ADDA) - Input & output (I/O) board - Power-off protection device for distribution panel - Hour meter - RS-485 interface - RJ-45 Ethernet interface - Sample power supply control terminal
SAMPLE SHELF & BRACKET	Test sample shelf: 2 stainless steel shelves, load capacity (uniformly distributed): 1kg for each.



● ● ● ● REFRIGERATION SYSTEM

WORKING MODE	Mechanical single refrigeration system (Air cooled)
REFRIGERATION COMPRESSOR	Hermetically sealed low-noise piston compressor
CONDENSER	Finned plate heat exchanger
EVAPORATOR	Finned plate heat exchanger (Dehumidifier)
THROTTLING DEVICE	Capillary & Electronic expansion valve (stepping motor driver)
REFRIGERATING MACHINE CONTROL METHOD	- The control system will automatically adjust the working condition of refrigeration machine in accordance with test conditions. - refrigeration system Compressor return air cooling circuit - Evaporative pressure adjustable valve
REFRIGERANT	R449a (ozone zero)

● ● ● ● HUMIDIFYING SYSTEM (MODEL MW3030 ONLY)

HUMIDIFIER	- Basin humidifying and heating - Stainless steel armored heater - Control method of heater: equivalent periodic pulse-width modulation without contact, SSR (solid-state relay) - Water level control device - Dry boil protector for heater
Water supply method	Lifted by water pump
Position of water supply device	Drawer type water tank on the front side
WATER TANK VOLUME	5L
WATER QUALITY	Resistivity $\geq 500\Omega\text{m}$




CONTROLLER

DISPLAY	7 inches, 800X480 dot matrix, TFT 64k color LCD display
OPERATING MODE	Program mode: fixed value mode
SETTING MODE	English menu; input via touch screen
PROGRAM CAPACITY	- Editable programs - Quantity: 20 max - Steps: 1000 max - Cycles: each step has a maximum of 20 cycles (each cycle step has a maximum of 99 cycles); - Fixed: 10 programs that can be linked
SET RANGE	- Temperature: adjust according to the temperature range of the equipment (Upper limit: +5°C; Lower limit: -5°C) - Humidity: (0~100) %RH
SET & DISPLAY RESOLUTION	- Temperature: 0.1°C - Time: 0.1min - Humidity: (0~100) %RH
INPUT	- Thermocouple - Platinum resistance, voltage, current, etc., if the equipment needs
COMMUNICATION INTERFACE	- RS-485 interface - RJ-45 Ethernet interface (IEEE802.3i/3u/3ab, 100Mbps)
INTERFACE CONVERTOR (OPTION)	- RS-232 interface: RS-485/ RS-232 convertor - GPIO interface (IEEE 488.2): RS-485/GPIB convertor
COMMUNICATION PROTOCOL	STEN Communication protocol
CONTROL MODE	- Anti-integral saturation PID - BTC (for temperature test equipment) - BTHC (for temperature and humidity test equipment)
CURVE RECORDING FUNCTION	- RAM with battery protection can save the set values, sampling values of equipment, and the time of sampling instant. The maximum recorded time is 350 days (when sampling period is 1.5min). - The test curve data recorded by controller is: 2 channel temperature: set temperature and measured temperature 2 channel humidity: set humidity and measured humidity.
AFFILIATED FUNCTION	- Malfunction alarm, cause and treatment indicating function; power failure protection function; highest and lowest temperature protection function; - Calendar timing function (automatic startup and shutdown) - Self-diagnosis function




FITOLOG SOFTWARE

The FitoLog software pack is a set of applications designed to facilitate the monitoring and programming and data from the FitoClima chambers. It consists of 3 applications: **FitoLog**, **FitoLogView** and **FitoProgram**.



FITOLOG

Records and displays in real time all data and details related to the set-points, running variables and equipment behaviour.



FITOPROGRAM

This application simplifies the creation of programs and its integration on the chamber ClimaPlus controller. Up to 20 programs, each with 50 segments, can be designed and linked to create detailed environmental profiles and simulations.

ACCESSORIES

- Additional shelves
- Observation window
- Instrument vehicle/table (850mm X 400mm) with casters



Let's meet!
aralab@aralab.pt
www.aralab.pt
T: +351 219 154 960



Control the environment
Your own climate